

Convir Pyropen Handheld Infrared Thermometer

- Conveniently clips into your pocket just like a pen
- Unique ultra compact design
- Wide temperature range
- High accuracy and repeatability
- Fast response
- Displays maximum, minimum, average and current temperatures
- Narrow field of view
- Optional laser sighting
- Optional data logging & data acquisition






The ultra compact Pyropen has been specifically designed to fit into your pocket, just like a pen, so that you can carry it with you anywhere you go. You simply aim, press the SCAN button and read the temperature immediately. No fuss. No need to focus and no special training. The non-contact nature of the measurement means that you can take the temperature of moving, rotating, inaccessible or hazardous objects. This makes the Pyropen particularly useful for test, inspection and maintenance applications in industries such as food & beverage, automotive, plastics & rubber, textiles, paper & packaging, chemicals & pharmaceuticals, HVAC, electrical, asphaltting, plus many others. The Pyropen L has all the features of the Pyropen E, plus laser sighting for small or distant targets and adjustable emissivity. The Pyropen D has all the features of the Pyropen L, plus a built-in memory for logging up to 12 temperatures and the ability to perform PC based data acquisition. It is supplied complete with PC interface cable and Calexlog software disk. High performance, low cost The Calex design team have taken advantage of the latest technology, not only to provide an ultra slim design but to incorporate reliability with high accuracy. Advanced manufacturing techniques are used to ensure that the Pyropen meets the highest quality standards at low cost. Each Pyropen comes with additional functions such as maximum, minimum and average temperature measurements. The Pyropen can be LOCKED into the ON position if continuous measurements are required. The last measured value can also be held for those situations where it is not easy to see the display whilst measuring.

GENERAL SPECIFICATIONS

MODEL	PYROPEN E	PYROPEN L/PYROPEN D
Temperature Range	-20°C to +500°C	-20°C to +500°C
Accuracy	+/-1% of reading or +/-1°C whichever is greater	+/-1% of reading or +/-1°C whichever is greater
Emissivity	Fixed at 0.95	Adjustable 0.3 to 1.0
Repeatability	+/-0.5% of reading or +/-0.5°C whichever is greater	+/-0.5% of reading or +/-0.5°C whichever is greater
Response Time, t90	500 ms (90% response)	500 ms (90% response)
Spectral Range	8 to 14 µm	8 to 14 µm
Ambient Temp Range	0°C to +50°C	0°C to +50°C
Housing	Pen style	Pen style
Sighting	None	Laser
Display	3.5 digit LCD	3.5 digit LCD
Power	2 x AAA batteries	2 x AAA batteries
Reading	°C or °F	°C or °F
Display Resolution	0.1°	0.1°
Field-of-view	8:1	8:1
Data Logging & Acquisition	None	Pyropen D only via Calexlog software supplied
Relative Humidity	10 to 95% non-condensing	10 to 95% non-condensing
Dimensions	163 mm x 27 mm x 16 mm	163 mm x 27 mm x 16 mm
Weight	50 g (excluding batteries)	60 g (excluding batteries)

APPLICATIONS



SOUTHERN TEMPERATURE SENSORS LTD.

Temperature Sensors, Accessories and Components

Unit 6, Weyside Park, Newman Lane, Alton, HANTS GU34 2PJ Tel: 01420 541422 Fax: 01420 541433
Email: enquiries@southerntemp.co.uk Website: www.southerntemp.co.uk